ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U. www.sodeca.com

ERP: Performance at the best efficiency point (BEP)

MC	Measurement category	**[m^3/h]**	Flow rate	**ηe [%]**	Efficiency
EC	Efficiency category	**[Pa]**	Static pressure / Total pressure	**N**	Efficiency grade
VSD	Variable Speed Drive	**[RPM]**	Speed	**[kw]**	Input power
SR	Specific ratio				

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m^3/h]	[Pa]	[RPM]
HBA-31-2T-0.75	Exclude. Gas Temp> 100°C									
HBA-31-2M-0.75	Exclude. Gas Temp> 100°C									
HBA-31-4T-0.37	Exclude. Gas Temp> 100°C									
HBA-31-4M-0.37	Exclude. Gas Temp> 100°C									
HBA-40-2T-1.5 IE3	Exclude. Gas Temp> 100°C									
HBA-40-2M-1.5	Exclude. Gas Temp> 100°C									
HBA-40-4T-0.5	Exclude. Gas Temp> 100°C									
HBA-45-2T-4 IE3	Exclude. Gas Temp> 100°C									
HBA-50-4T-1 IE3	Exclude. Gas Temp> 100°C									
HBA-63-4T-1.5 IE3	Exclude. Gas Temp> 100°C									
HBA-71-4T-5.5 IE3	Exclude. Gas Temp> 100°C									
HBA-71-6T-0.75	Exclude. Gas Temp> 100°C									
HBA-80-6T-1.5 IE3	Exclude. Gas Temp> 100°C									
HBA-100-6T-1.5 IE3	Exclude. Gas Temp> 100°C									