

ECODESIGN INFORMATION

Applies to residential ventilation units (RVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

| | | | | | | |
|---|--|--|--|--|--|--|
| a) Brand | SODECA, SLU | SODECA, SLU | SODECA, SLU | SODECA, SLU | SODECA, SLU | SODECA, SLU |
| b) Model | CA/LINE-10 | CA/LINE-12 | CA/LINE-15 | CA/LINE-16 | CA/LINE-20 | CA/LINE-25 |
| c) Specific energy consumption (SEC) average climate (kWh/(m ² .yr)) | -23.7 | -24.2 | -24.8 | -25 | -24 | -24.1 |
| c) Specific energy consumption (SEC) cold climate (kWh/(m ² .yr)) | -50.8 | -51.2 | -51.8 | -52.1 | -51 | -51.2 |
| c) Specific energy consumption (SEC) warm climate (kWh/(m ² .yr)) | -8.2 | -8.7 | -9.3 | -9.5 | -8.5 | -8.6 |
| c) SEC class | C | C | C | C | C | C |
| d) Typology | RVU / UVU | RVU / UVU | RVU / UVU | RVU / UVU | RVU / UVU | RVU / UVU |
| e) Drive type | Multi-speed | Multi-speed | Multi-speed | Multi-speed | Multi-speed | Multi-speed |
| f) HRS type | None | None | None | None | None | None |
| g) Thermal efficiency of heat recovery (%) | | | | | | |
| h) Maximum flow rate (m ³ /h) | 210 | 259 | 381 | 408 | 857 | 922 |
| i) Electric power input of the fan drive at maximum flow rate (W) | 41 | 46 | 58 | 57 | 158 | 164 |
| j) Sound power level (LWA) (dBA) | 61 | 63 | 63 | 63 | 69 | 69 |
| k) Reference flow rate (m ³ /s) | 0.041 | 0.05 | 0.074 | 0.079 | 0.167 | 0.179 |
| l) Reference pressure difference (Pa) | 208 | 198 | 210 | 226 | 295 | 295 |
| m) SPI (W/m ³ /h) | 0.28 | 0.25 | 0.22 | 0.2 | 0.26 | 0.26 |
| n) Control factor | 0.65 | 0.65 | 0.65 | 0.65 | 0.65 | 0.65 |
| n) Control typology | Local demand control | Local demand control | Local demand control | Local demand control | Local demand control | Local demand control |
| o) Declared max. internal leakage rate (%) | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 |
| o) Max. external leakage rate (%) | 3.2 | 2.7 | 1.8 | 1.7 | 0.8 | 0.7 |
| p) Mixing rate | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| q) Position and description of visual filter warning | Not applicable | Not applicable | Not applicable | Not applicable | Not applicable | Not applicable |
| r) Instructions to install regulated grilles | See manual | See manual | See manual | See manual | See manual | See manual |
| s) Website | www.sodeca.com | www.sodeca.com | www.sodeca.com | www.sodeca.com | www.sodeca.com | www.sodeca.com |
| t) Airflow sensitivity to pressure variations at +20 Pa and -20 Pa | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| u) Indoor/outdoor air tightness | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| v) Annual electricity consumption (AEC) average climate (kWh/yr) | 200 | 200 | 100 | 100 | 200 | 200 |
| v) Annual electricity consumption (AEC) warm climate (kWh/yr) | 200 | 200 | 100 | 100 | 200 | 200 |
| v) Annual electricity consumption (AEC) cold climate (kWh/yr) | 200 | 200 | 100 | 100 | 200 | 200 |
| w) Annual heating saved (AHS) average climate (kWh/yr) | 2800 | 2800 | 2800 | 2800 | 2800 | 2800 |
| w) Annual heating saved (AHS) warm climate (kWh/yr) | 1300 | 1300 | 1300 | 1300 | 1300 | 1300 |
| w) Annual heating saved (AHS) cold climate (kWh/yr) | 5500 | 5500 | 5500 | 5500 | 5500 | 5500 |
| ErP compliance | 2018 | 2018 | 2018 | 2018 | 2018 | 2018 |