

ECODESIGN INFORMATION

www.sodeca.com

I samsvar med EU-kommisjonens forordning (EU) 2024/1834 om gjennomføring av Europaparlamentsdirektiv 2009/125/EF

SODECA, S.L.U.

- a) viftetype

b) viftevirkningsgrad [%]

c) VSD lagt til grunn i dataene

d) målekategori
- e) effektivitetskategori

f) N fan

g1) Pe [kW]

g2) qv [m³/h]
- g3) Δp [Pa]

h1) vifte for dobbelt bruk

h2) reversibel vifte

h3) vifte med lavt støynivå
- i) likespenning under 100 V

k) oBEP

l) viftehastighet [o/min]

m) spesifikt forhold
- j) p) q) viktige elementer, informasjon om demontering og resirkulering i produktmanuale

Modell	a)	b)	c)	d)	e)	f)	g1)	g2)	g3)	h1)	h2)	h3)	i)	k)	l)	m)
HTM/ATEX-35-2T/2G Ex db										ErP Exclude. Pe < 750 W						
HTM/ATEX-35-4T/2G Ex db										ErP Exclude. Pe < 750 W						
HTM/ATEX-40-4T/2G Ex db										ErP Exclude. Pe < 750 W						
HTM/ATEX-45-4T/2G Ex db										ErP Exclude. Pe < 750 W						
HTM/ATEX-56-4T/2G Ex db										ErP Exclude. Pe < 750 W						
HTM/ATEX-63-4T/2G Ex db										ErP Exclude. Pe < 750 W						
HTM/ATEX-35-2T/2G Ex eb										ErP Exclude. Pe < 750 W						
HTM/ATEX-35-4T/2G Ex eb										ErP Exclude. Pe < 750 W						
HTM/ATEX-40-4T/2G Ex eb										ErP Exclude. Pe < 750 W						
HTM/ATEX-45-4T/2G Ex eb										ErP Exclude. Pe < 750 W						
HTM/ATEX-56-4T/2G Ex eb										ErP Exclude. Pe < 750 W						
HTM/ATEX-63-4T/2G Ex eb										ErP Exclude. Pe < 750 W						
HTM/ATEX-35-2T/2D Ex tb										ErP Exclude. Pe < 750 W						
HTM/ATEX-35-4T/2D Ex tb										ErP Exclude. Pe < 750 W						
HTM/ATEX-40-4T/2D Ex tb										ErP Exclude. Pe < 750 W						
HTM/ATEX-45-4T/2D Ex tb										ErP Exclude. Pe < 750 W						
HTM/ATEX-56-4T/2D Ex tb										ErP Exclude. Pe < 750 W						
HTM/ATEX-63-4T/2D Ex tb										ErP Exclude. Pe < 750 W						