ECODESIGN INFORMATION

Applies to residential ventilation units (RVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

a) Brand	SODECA, SLU	SODECA, SLU	SODECA, SLU	SODECA, SLU	SODECA, SLU	SODECA, SLU	SODECA, SLU
b) Model	CRF-225-4M	CRF-250-4M	CRF-250-4T	CRF-315-6T	CRF-315-6M	CRF-355-6T	CRF-355-6M
c) Specific energy consumption (SEC) average climate (kWh/(m².yr))	-25.3	-25	-25.5	-26	-25.5	-26.1	-26.1
c) Specific energy consumption (SEC) cold climate (kWh/(m².yr))	-52.3	-52	-52.5	-53.1	-52.6	-53.1	-53.1
c) Specific energy consumption (SEC) warm climate (kWh/(m².yr))	-9.8	-9.5	-10	-10.5	-10	-10.6	-10.5
c) SEC class	C	C	C	C	C	B	B
d) Typology	RVU / UVU	RVU / UVU	RVU / UVU	RVU / UVU	RVU / UVU	RVU / UVU	RVU / UVU
e) Drive type	Variabel hastighet	Variabel hastighet	Variabel hastighet	Variabel hastighet	Variabel hastighet	Variabel hastighet	Variabel hastighet
f) HRS type	Ingen	Ingen	Ingen	Ingen	Ingen	Ingen	Ingen
g) Thermal efficiency of heat recovery (%)							
h) Maximum flow rate (m³/h)	328	501	501	659	659	992	992
i) Electric power input of the fan drive at maximum flow rate (W)	53	86	72	80	95	118	118
j) Sound power level (LWA) (dBA)	61	62	62	58	58	62	62
k) Reference flow rate (m³/s)	0.064	0.097	0.097	0.128	0.128	0.193	0.193
l) Reference pressure difference (Pa)	50	50	50	50	50	50	50
m) SPI (W/m³/h)	0.229	0.252	0.214	0.172	0.209	0.168	0.17
n) Control factor	0.65	0.65	0.65	0.65	0.65	0.65	0.65
n) Control typology	Lokal etterspørselskontroll	Lokal etterspørselskontroll	Lokal etterspørselskontroll	Lokal etterspørselskontroll	Lokal etterspørselskontroll	Lokal etterspørselskontroll	Lokal etterspørselskontroll
o) Declared max. internal leakage rate (%)	0.0	0.0	0.0	0.0	0.0	0.0	0.0
o) Max. external leakage rate (%)	1.0	2.1	1.7	1.8	2.3	3.0	3.0
p) Mixing rate	0.00	0.00	0.00	0.00	0.00	0.00	0.00
q) Position and description of visual filter warning	Se manual	Se manual	Se manual	Se manual	Se manual	Se manual	Se manual
r) Instructions to install regulated grilles	Se manual	Se manual	Se manual	Se manual	Se manual	Se manual	Se manual
s) Website	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com	www.sodeca.com
t) Airflow sensitivity to pressure variations at +20 Pa and –20 Pa	0.00	0.00	0.00	0.00	0.00	0.00	0.00
u) Indoor/outdoor air tightness	0.00	0.00	0.00	0.00	0.00	0.00	0.00
v) Annual electricity consumption (AEC) average climate (kWh/yr)	121	133	113	91	110	88	89
v) Annual electricity consumption (AEC) warm climate (kWh/yr)	121	133	113	91	110	88	89
v) Annual electricity consumption (AEC) cold climate (kWh/yr)	121	133	113	91	110	88	89
w) Annual heating saved (AHS) average climate (kWh/yr)	2830	2830	2830	2830	2830	2830	2830
w) Annual heating saved (AHS) warm climate (kWh/yr)	1280	1280	1280	1280	1280	1280	1280

ECODESIGN INFORMATION

Applies to residential ventilation units (RVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

w) Annual heating saved (AHS) cold climate (kWh/yr)	5536	5536	5536	5536	5536	5536	5536
ErP compliance	2018	2018	2018	2018	2018	2018	2018