ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U. www.sodeca.com

ERP: Performance at the best efficiency point (BEP)

MC	Measurement category	**[m^3/h]**	Flow rate	**ηe [%]**	Efficiency
EC	Efficiency category	**[Pa]**	Static pressure / Total pressure	**N**	Efficiency grade
VSD	Variable Speed Drive	**[RPM]**	Speed	**[kw]**	Input power
SR	Specific ratio				

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m^3/h]	[Pa]	[RPM]
CI-50-4/8T-F-400	A	Statisch	VSD niet nodig	1.00	37.5	58.6	1.611	6050	0	1395
CI-75-4/8T-F-400	A	Statisch	VSD niet nodig	1.00	36.2	53.7	2.803	8080	0	1450
CI-100-4/8T-F-400	A	Statisch	VSD niet nodig	1.00	47.2	63.6	3.311	9340	0	1445
CI-50-4/8T-F-300	A	Statisch	VSD niet nodig	1.00	36.5	57.4	1.656	6050	0	1395
CI-75-4/8T-F-300	A	Statisch	VSD niet nodig	1.00	36.2	53.7	2.803	8080	0	1450
CI-100-4T-F-300	A	Statisch	VSD niet nodig	1.00	56.7	74.2	2.759	9340	0	1445
CI-100-4/8T-F-300	A	Statisch	VSD niet nodig	1.00	47.3	63.7	3.301	9340	0	1445