INFORMAÇÃO DE CONCEÇÃO ECOLÓGICA

Com base no Regulamento (UE) nº 327/2011 da Comissão Europeia, que aplica a diretiva 2009/125/CE do Parlamento Europeu
Aplicável a ventiladores

SODECA, S.L.U. www.sodeca.com

ERP: Características do ponto de eficiência máxima (BEP)

MC	Categoria de medição	**[m^3/h]**	Fluxo	**ηe [%]**	Rendimento
EC	Categoria eficiência	**[Pa]**	Pressão estática / Pressão total	**N**	Grau eficiência
VSD	Variador de velocidade	**[RPM]**	Velocidade	**[kw]**	Potência eléctrica
SR	Relação específica				

Modelo	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m^3/h]	[Pa]	[RPM]
KIT BOXSMART-2880 - 230V-1D	Isento ErP									
KIT BOXSMART-7100 - 230V-1D	Isento ErP									
KIT BOXSMART-7800 - 230V-1D	Isento ErP									
KIT BOXSMART-12900 - 230V-1D	Isento ErP									
KIT BOXSMART-17000 - 230V-1D	Isento ErP									
KIT BOXSMART-7800 - 400V-1D	Isento ErP									
KIT BOXSMART-12900 - 400V-1D	Isento ErP									
KIT BOXSMART-17000 - 400V-1D	Isento ErP									
KIT BOXSMART-21100 - 400V-1D	Isento ErP									
KIT BOXSMART-2880 - 230V-2D	Isento ErP									
KIT BOXSMART-7100 - 230V-2D	Isento ErP									
KIT BOXSMART-7800 - 230V-2D	Isento ErP									
KIT BOXSMART-12900 - 230V-2D	Isento ErP									
KIT BOXSMART-17000 - 230V-2D	Isento ErP									
KIT BOXSMART-7800 - 400V-2D	Isento ErP									
KIT BOXSMART-12900 - 400V-2D	Isento ErP									
KIT BOXSMART-17000 - 400V-2D	Isento ErP									
KIT BOXSMART-21100 - 400V-2D	Isento ErP									