

ECODESIGN INFORMATION

Applies to non-residential ventilation units (NRVU)

According to Regulation EU No 1253/2014 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

www.sodeca.com

b) Model	f) Thermal efficiency of heat recovery (%)	j) Face velocity at design flow rate	n) Static efficiency of fans according to (EU) 327/2011
c) Typology	g) Nominal flowrate	k) Nominal external pressure	q) Visual filter warning
d) Drive type	h) Effective electric power input	l) Internal pressure drop of ventilation components	r) LWA radiated
e) HRS type	i) SFPint	m) Internal pressure drop of non-ventilation components	o1) Max. internal leakage rate
			o2) Max. external leakage rate
			p) Energy performance of the filters

b)	c)	d)	e)	f)	g)	h)	i)	j)	k)	l)	m)	n)	o1)	o2)	p)	q)	r)	ERP
CJBD/EC/C-1919-4M-1/5 IE4	NRVU / UVU	Viteza variabila	Nimic	0.204	0.111	230	4.30	196			36.3	2.4					dBA	
CJBD/EC/C-1919-6M-1/10 IE4	NRVU / UVU	Viteza variabila	Nimic	0.138	0.034	230	2.90	76			31.9	2.4					73	2018
CJBD/EC/C-2525-4M-1/2 IE4	NRVU / UVU	Viteza variabila	Nimic	0.458	0.320	230	5.90	314			43.6	2.4					77	2018
CJBD/EC/C-2525-4M-3/4 IE4	NRVU / UVU	Viteza variabila	Nimic	0.441	0.313	230	5.60	305			41.8	2.4					81	2018
CJBD/EC/C-2525-4M-1 IE4	NRVU / UVU	Viteza variabila	Nimic	0.371	0.263	230	4.80	309			43.2	2.4					74	2018
CJBD/EC/C-2525-6M-1/3 IE4	NRVU / UVU	Viteza variabila	Nimic	0.281	0.090	230	3.60	124			38.5	2.4					72	2018
CJBD/EC/C-2828-4M-1 IE4	NRVU / UVU	Viteza variabila	Nimic	0.626	0.571	230	6.60	434			45.3	2.4					65	2018
CJBD/EC/C-2828-4M-2 IE4	NRVU / UVU	Viteza variabila	Nimic	0.649	0.632	230	6.80	409			40.5	2.4					69	2018
CJBD/EC/C-2828-6M-1/3 IE4	NRVU / UVU	Viteza variabila	Nimic	0.405	0.157	230	4.30	147			41.9	2.4					72	2018
CJBD/EC/C-3333-6M-1 IE4	NRVU / UVU	Viteza variabila	Nimic	0.662	0.454	230	4.90	262			37.3	2.4					81	2018