

INFORMATION OM EKODESIGN

Enligt Europeiska kommissionens förordning nr 327/2011 som tillämpar Europaparlamentets direktiv 2009/125/EG
Tillämpas på fläktar

SODECA, S.L.U.

www.sodeca.com

ERP: Prestanda vid bästa effektivitetspunkt (BEP)

MC	Mättningskategori
EC	Effektivitetskategori
VSD	Variabel hastighet
SR	Specifikt förhållande

[m³/h]	Flödeshastighet
[Pa]	Statiskt tryck/totalt tryck
[RPM]	Hastighet

ηe [%]	Effektivitet
N	Effektivitetsgrad
[kW]	Ineffekt

Modell	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m³/h]	[Pa]	[RPM]
CHT/ATEX-200-4T/2G Ex db					ErP: Utesl. ATEX					
CHT/ATEX-225-4T/2G Ex db					ErP: Utesl. ATEX					
CHT/ATEX-250-4T/2G Ex db					ErP: Utesl. ATEX					
CHT/ATEX-315-4T/2G Ex db					ErP: Utesl. ATEX					
CHT/ATEX-315-6T/2G Ex db					ErP: Utesl. ATEX					
CHT/ATEX-400-4T/2G Ex db					ErP: Utesl. ATEX					
CHT/ATEX-400-6T/2G Ex db					ErP: Utesl. ATEX					
CHT/ATEX-450-4T/2G Ex db					ErP: Utesl. ATEX					
CHT/ATEX-450-6T/2G Ex db					ErP: Utesl. ATEX					
CHT/ATEX-500-6T/2G Ex db					ErP: Utesl. ATEX					
CHT/ATEX-560-6T/2G Ex db					ErP: Utesl. ATEX					
CHT/ATEX-630-6T/2G Ex db					ErP: Utesl. ATEX					
CHT/ATEX-200-4T/2G Ex eb					ErP: Utesl. ATEX					
CHT/ATEX-225-4T/2G Ex eb					ErP: Utesl. ATEX					
CHT/ATEX-250-4T/2G Ex eb					ErP: Utesl. ATEX					
CHT/ATEX-315-4T/2G Ex eb					ErP: Utesl. ATEX					
CHT/ATEX-315-6T/2G Ex eb					ErP: Utesl. ATEX					
CHT/ATEX-400-4T/2G Ex eb					ErP: Utesl. ATEX					
CHT/ATEX-400-6T/2G Ex eb					ErP: Utesl. ATEX					
CHT/ATEX-450-4T/2G Ex eb					ErP: Utesl. ATEX					
CHT/ATEX-450-6T/2G Ex eb					ErP: Utesl. ATEX					
CHT/ATEX-500-6T/2G Ex eb					ErP: Utesl. ATEX					
CHT/ATEX-560-6T/2G Ex eb					ErP: Utesl. ATEX					
CHT/ATEX-630-6T/2G Ex eb					ErP: Utesl. ATEX					