INFORMATION OM EKODESIGN

www.sodeca.com

Enligt kommissionens förordning (EU) 2024/1834 om genomförande av Europaparlamentets direktiv 2009/125/EG

SODECA, S.L.U.

a) fläkttyp
b) fläktverkningsgrad [%]
c) VSD antagen i data
d) mätkategori
e) verkningsgradskategori
f) N fan
g1) Pe [kW]
g2) qv [m³/h]
g3) Δp [Pa]
h1) fläkt för dubbla användningsområden
h2) reversibel fläkt
h3) fläkt med låg ljudnivå
i) likspänning under 100 V
k) σBEP
l) fläkthastighet [rpm]
m) specifikt förhållande
j) p) q) väsentliga delar, information om demontering och återvinning i produktmanualen

Modell	a)	b)	c)	d)	e)	f)	g1)	g2)	g3)	h1)	h2)	h3)	i)	k)	l)	m)
HTM/ATEX-35-2T/2G Ex db	*ErP: Uteslut. ATEX*															
HTM/ATEX-35-4T/2G Ex db	*ErP: Uteslut. ATEX*															
HTM/ATEX-40-4T/2G Ex db	*ErP: Uteslut. ATEX*															
HTM/ATEX-45-4T/2G Ex db	*ErP: Uteslut. ATEX*															
HTM/ATEX-56-4T/2G Ex db	*ErP: Uteslut. ATEX*															
HTM/ATEX-63-4T/2G Ex db	*ErP: Uteslut. ATEX*															
HTM/ATEX-35-2T/2G Ex eb	*ErP: Uteslut. ATEX*															
HTM/ATEX-35-4T/2G Ex eb	*ErP: Uteslut. ATEX*															
HTM/ATEX-40-4T/2G Ex eb	*ErP: Uteslut. ATEX*															
HTM/ATEX-45-4T/2G Ex eb	*ErP: Uteslut. ATEX*															
HTM/ATEX-56-4T/2G Ex eb	*ErP: Uteslut. ATEX*															
HTM/ATEX-63-4T/2G Ex eb	*ErP: Uteslut. ATEX*															
HTM/ATEX-35-2T/2D Ex tb	*ErP: Uteslut. ATEX*															
HTM/ATEX-35-4T/2D Ex tb	*ErP: Uteslut. ATEX*															
HTM/ATEX-40-4T/2D Ex tb	*ErP: Uteslut. ATEX*															
HTM/ATEX-45-4T/2D Ex tb	*ErP: Uteslut. ATEX*															
HTM/ATEX-56-4T/2D Ex tb	*ErP: Uteslut. ATEX*															
HTM/ATEX-63-4T/2D Ex tb	*ErP: Uteslut. ATEX*															